



## D-A COARSE EXTREME CUT MICROFIBER PAD

The D-A COARSE EXTREME CUT microfiber pad for Dual Action polishers is specially designed to rapidly remove severe defects, sanding marks, scratches on fully cured or harder paint systems, and flat solid surfaces. The density and lateral stability of the foam interface, coupled with the specialized microfiber material, means fast cutting for dual-action random orbital and gear-driven orbital tools. Pair with RUPES D-A COARSE compound and experience our fastest defect removal for any of our dual-action BigFoot polishing tools.

### CUT/GLOSS



### TIPS FOR SUCCESS

- Prime the pad by applying a thin, even layer of compound to the face before the first use
- Reload the pad with small amounts of compound, typically only a few drops. Over-saturating the pad with compound can lead to diminished performance
- Clean pads frequently during use with compressed air, a vacuum, or RUPES Claw Pad Tool to maintain consistent performance
- After use, clean with warm water and a mild soap, rinse well to remove residues, air dry
- Best use on factory-applied paint. Not recommended on fresh paint
- Not recommended for use with rotary tools
- Apply up to 30/45 second cycle time in an area no larger than six times the pad diameter
- Use minimum two pads per vehicle, swapping in 15 minutes intervals

### RECOMMENDED COMPOUNDS

D-A COARSE



MILLE COARSE



MILLE COARSE  
BLACK LINE




XC-2



### RECOMMENDED POLISHERS


**Random orbital Polishers:** iBrid Series (HLR 21-15, HLR75 Mini, Nano) LHR21 Series, LHR15 Series, LHR75E Mini, LHR12E Duetto,  
**Gear Driven:** LK900E



RANDOM ORBITAL



GEAR DRIVEN



PAD PROFILE

PADS CODES	SIZES
9.MF80H	Ø85 mm (3")
9.MF135H	Ø135 mm (5")
9.MF160H	Ø160 mm (6")

### INDUSTRIES & APPLICATIONS

