



D-A COARSE

HIGH PERFORMANCE COARSE CUTTING FOAM PAD

The D-A COARSE foam pad is specially designed to be used with both random orbital and gear-driven tools. The unique open-cell foam material removes mild to severe defects from most paint systems when paired with RUPES D-A COARSE compound.

CUT/GLOSS



TIPS FOR SUCCESS

- Clean pads frequently during use with compressed air, a vacuum, or RUPES Claw Pad Tool to maintain consistent performance
- Do not over-saturate the pad with compound. Too much compound can lead to diminished performance
- After use clean with warm water and a mild soap, rinse well to remove residues, air dry
- Avoid the use of solvent-based compounds and cleaners to prevent damage to the foams cell structure

RECOMMENDED COMPOUNDS

D-A COARSE



MILLE COARSE



MILLE COARSE
BLACK LINE




XC-2



RECOMMENDED POLISHERS

Random Orbital Polishers: iBrid Series (HLR 21-15, HLR75 Mini, Nano) LHR21 Series, LHR15 Series, LHR75E Mini, LHR12E Duetto,
Gear Driven Polishers: LK900E



PADS CODES	SIZES
9.DA40H	Ø35-40mm (1"-1.5")
9.DA70H	Ø50-70mm (2"-3")
9.DA100H	Ø80-100mm (3"-4")
9.DA150H	Ø130-150mm (5"-6")
9.DA180H	Ø150-180mm (6"-7")

INDUSTRIES & APPLICATIONS

