



D-A FINE MICROFIBER POLISHING PAD

The D-A FINE ,microfiber polishing pads for Dual Action polishers, are specially designed for the removal of moderate defects, swirls, haze and holograms on fully cured paint. Specialized microfiber material bonded to a semi-flexible foam backing allow for better control and contouring over varied panel shapes with an ideal balance of cutting and finishing ability. Combined with RUPES D-A FINE compound, the D-A FINE microfiber pad delivers quick removal of moderate defects and a high degree of finish quality on most paint systems.

▶ CUT/GLOSS

CUT



GLOSS



▶ TIPS FOR SUCCESS

- Prime the pad by applying a thin, even layer of compound to the face before the first use
- Reload the pad with small amounts of compound, typically only a few drops. Over-saturating the pad with compound can lead to diminished performance
- Clean pads frequently during use with compressed air, a vacuum, or RUPES Claw Pad Tool to maintain consistent performance
- After use, clean with warm water and a mild soap, rinse well to remove residues, air dry
- Best use on factory-applied paint
- Not recommended on fresh paint. Not recommended for use with rotary tools
- Apply up to 30/45 second cycle time in an area no larger than six times the pad diameter
- Use minimum two pads per vehicle, swapping in 15 minutes intervals

▶ RECOMMENDED COMPOUNDS

D-A FINE



MILLE FINE



UNO PROTECT




UNO ADVANCED



▶ RECOMMENDED POLISHERS


Random orbital Polishers: iBrid Series (HLR 21-15, HLR75 Mini, Nano) LHR21 Series, LHR15 Series, LHR75E Mini, LHR12E Duetto,
Gear Driven: LK900E



RANDOM ORBITAL



GEAR DRIVEN



PAD PROFILE

PADS CODES	SIZES
9.MF80M	Ø85 mm (3")
9.MF135M	Ø135 mm (5")
9.MF160M	Ø160 mm (6")

INDUSTRIES & APPLICATIONS

