

ROTARY COARSE WOOL POLISHING PAD

FOR ROTARY POLISHERS

Designed to provide impressive cutting speed, reduced risk of rotary swirls and improved process efficiency while maintaining a smooth, vibration-free, operator experience. The RUPES twisted natural wool pads for rotary are available in three sizes and are compatible with virtually all rotary polishing tools on the market today. Each RUPES twisted natural wool pad is constructed of a premium blend of 100% natural lamb's wool. No synthetic fibers or fillers are used in the construction of the pad and each strand is steam set to ensure consistency and fastness of color. The RUPES twisted natural wool pads were developed to optimize the performance of RUPES ROTARY COARSE compound in a variety of applications and industries.

▷ CUT/GLOSS

CUT 

GLOSS 

▷ TIPS FOR SUCCESS

- Pair this pad with RUPES ROTARY COARSE compound
- Always prime the pad first to ensure a smooth experience from initial application
- Use small amounts of compound to reload the pad; oversaturating will lead to diminished performance
- Clean pads frequently during use with compressed air, a vacuum, or RUPES Claw Pad Tool to maintain consistent performance
- Using metal spurs are hard tools to clean pads will cause damage and shorten pad life.
- After use: clean with warm water and a mild soap, rinse well to remove residues, air dry

▷ RECOMMENDED COMPOUNDS

ROTARY COARSE



ROTARY COARSE
BLACK LINE





XC-2



▷ RECOMMENDED POLISHERS

Rotary Polisher: LH19E

PADS CODES	SIZES
9.BL230H	Ø165mm (6.5")
9.BL200H	Ø150mm (Ø6")
9.BL180H	Ø125mm (Ø5")



INDUSTRIES & APPLICATIONS



NOTE: All pads are individually packaged in a transparent flow pack for UV / dust / humidity protection